

Terra 2 & 3 Tandem Sled Base Chair



SPECIFICATIONS



Model	Weight	22" 2 Seat	22" 3 Seat
22" TC1/TE1	Open Arm	93 lbs	154.5 lbs
30" TC2/TE2	Half Arm	115.5 lbs	184.5 lbs
Dimensions	Full Arm	138 lbs	214.5 lbs
Seat Height		30" 2 Seat	30" 3 Seat
Overall Height	19"	Open Arm	118.6 lbs
Overall Depth	34.8"	Half Arm	141.1 lbs
22" 2 Seat Width	50.5"	Full Arm	163.6 lbs
30" 2 Seat Width	66.5"		252.9 lbs
22" 3 Seat Width	74.5"		
30" 3 Seat Width	98.5"		

*Intended for indoor use only

See page 2 for COM information.



DETAILS

Finishes

See Design Guide for finish options.

*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

Options

Available in California TB133 compliant upholstery. Bolt-down plate.

Ballasting available:

25 lb plate for 22" Chair

35 lb plate for 30" Chair

*Ballasting must be communicated at time of order.

Assembly

No assembly required

Fabrication & Material

Frame: Welded steel arm frames

Cushions: Constructed of a 2.0 lb density seat foam wrapped in fabric with concealed staples.

Arm Caps: Hardwood (Maple, Teak, or Walnut color) or polyurethane in Raven

Arm Options: Open, Half Arm, & Full arm panels are MDF, foam & fabric

Glides: Non-removable Nylon Glides with secure hardware

Installation

Required for bolt-down

Warranty

10 year limited replacement

Maintenance

Frame: Norix recommends the use of soap and water or cleaner made for stainless steel for both regular and deep cleaning.

Upholstery: Refer to upholstery manufacturer's cleaning instructions for specific fabric.

TESTING

Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.
- Compliant with Healthier Hospitals guidelines

Performance Test Standards

- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- Meets or exceeds the requirements of ANSI/BIFMA X5.4-2012
- Tested to 750 lb static load
- Product dynamic drop tested to a relative impact force of two times BIFMA 5.4 15.4.2 (250 lbs from 18")

COM YARDS

TC1 - 22" Open Arm Chair

Total Yards 4.6
 Seat Yards 2
 Back Yards 2.6

TC1 - 22" Half Arm Chair

Total Yards 7.15
 Seat Yards 2
 Back Yards 2.6
 Arm Yards 2.55

TC1 - 22" Full Arm Chair

Total Yards 9.58
 Seat Yards 2
 Back Yards 2.6
 Arm Yards 4.98

TE1 - 22" Open Arm Chair

Total Yards 6.9
 Seat Yards 3
 Back Yards 3.9

TE1 - 22" Half Arm Chair

Total Yards 10.3
 Seat Yards 3
 Back Yards 3.9
 Arm Yards 3.4

TE1 - 22" Full Arm Chair

Total Yards 13.54
 Seat Yards 3
 Back Yards 3.9
 Arm Yards 6.64

TC2 - 22" Open Arm Chair

Total Yards 5.6
 Seat Yards 2
 Back Yards 3.6

TC2 - 22" Half Arm Chair

Total Yards 9
 Seat Yards 2
 Back Yards 3.6
 Arm Yards 3.4

TC2 - 22" Full Arm Chair

Total Yards 10.58
 Seat Yards 2
 Back Yards 3.6
 Arm Yards 4.98

TE2 - 22" Open Arm Chair

Total Yards 8.4
 Seat Yards 3
 Back Yards 5.4

TE2 - 22" Half Arm Chair

Total Yards 11.8
 Seat Yards 3
 Back Yards 5.4
 Arm Yards 3.4

TE2 - 22" Full Arm Chair

Total Yards 15.04
 Seat Yards 3
 Back Yards 5.4
 Arm Yards 6.64